



20W LED H80 Lamp - 5000K

Item # 665

L20H80/50K

1 LAMP SPECIFICATION			
1-1	Lamp Type	LED H80	
1-2	Dimmable (Y/N)	NO	
1-3	Base	E26	
1-4	Lamp Finish/Type	H80	
1-5	Lamp Wattage	20W	
1-6	Wattage Comparison (FC on Floor)	250 Incand. (55W CFL)	
1-7	Rated Average Life (hours) L70	50,000	
1-8	Reliable Operating Temperature	-4F to 113F	
2 Photometric Characteristics			
2-1	Initial Lumens	2700	
2-2	Centre Beam Candle Power (Cd)	605	
2-3	Beam Angle (50% I Max) in Degree	140	
2-4	Beam Angle (10% I Max) in Degree	220	
2-5	Initial Lumens per Watt	135	
2-6	Color Temperature	5000K	
2.7	Color Rendering Index (CRI)	80	
3 Electrical Characteristics			
3-1	Input Line Voltage/Frequency	120V/277V 50/60 Hz	3-2 Power Factor >0.90
3-3	Lamp rated Wattage	20W	3-4 Input Line Current 180mA(120V) 80mA(277V)
3-5	Total Harmonic Distortion	<30%(120V), <20% (277V)	3-6 Dimming Range in % Not Dimmable
4 Dimensional Characteristics			
4-1	Nominal Length (Inches/mm)	6.69" / 170 mm	4-2 Diameter 3.15" / 80 mm
5 Product Information			
5-1	Description	20W LED H80 Lamp - 5000K	
5-2	Primary Application	Commercial, Industrial, Agriculture	
5-3	Warranty	5 Years from date of purchase	
5-4	TCLP Compliant	YES	5-6 RoHS Compliant YES
5-5	Energy Star or LM79 (Y/N)	LM79	5-8 ETL- (Wet Location) YES
6 PACKING DETAILS			
6-1	Color Box Size (Inches)	1x1 3.3 x 3.3 x 7.3	6-2 Inner Carton Size (Inches) N/A
6-3	Master Carton Size (Inches)	1x12 14.17 x 10.63 x 7.87	6-4 Gross Weight / Net Weight (lbs) 8.49 / 5.61



01/2017© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.