

11W LED Long Neck PAR30 Dimmable - 5000K

ltem # 718

L11PAR30LNDIM/50K

1	1 LAMP SPECIFICATION						
1-1	Lamp Type		LED PAR30				
1-2	Dimmable (Y/N)		YES				
1-3	Base		E26				
1-4	Lamp Finish/Type	PAR30					
1-5	Lamp Wattage		11W				
1-6	Wattage Comparison (FC on Floor)		75W Incand				
1-7	Rated Average Life (hours) L70		25,000		ſ		
1-9	Reliable Operating Temperature	-4F to 113F Øverdrive					
2	Photometric Characteristics						
2-1	Initial Lumens	900					
2-2	Centre Beam Candle Power (Cd)		1600				
2-3	Beam Angle (50% I Max) in Degree		40(Flood)			Entre	
2-4	Beam Angle (10% I Max) in Degree		N/A		c (VL) us	Bompliant	
2-5	Initial Lumens per Watt		82				
2-6	Color Temperature		5000K				
2.7	Color Rendering Index (CRI)		80				
3	Electrical Characteristics						
3-1	Input Line Voltage/Frequency		120V 60 Hz	3-2	Power Factor	0.94	
3-3	Lamp rated Wattage		11W	3-4	Input Line Current	110 mA	
3-5	Total Harmonic Distortion		25%	3-6	Dimming Range in %	Full	
4	Dimensional Characteristics						
4-1	Nominal Length (Inches/mm)		4.56"/116mm	4-2	Diameter	3.74"/95mm	
5	Product Information						
5-1	Description	scription 11W LED High CRI PAR30 Flood Dimmable - 5000K					
5-2	Primary Application	Household	Use, Office & Commercial				
5-3	Warranty 5 Years fro		om date of purchase				
5-4	TCLP Compliant YES			5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N) No			5-8	UL / FCC	YES	
6	6 PACKING DETAILS						
6-1	Color Box Size (Inches) 1x1 3.9 x 3.9 x 4.		9	6-2	Inner Carton Size (Inches) 1x6	12.20 x 8.15 x 5.24	
6-3	Master Carton Size (Inches) 1x12 17.24 x 12.99		9 x 6.61	6-4	Gross Weight / Net Weight (lbs)	5.07 / 3.13	
	04/2021© Overdrive For more information visit www.overdrive-lighting.com						
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.							