

17W LED PAR38 Dimmable FLOOD - 5000K

ltem # 720

L17PAR38DIM/FL/50K

1	LAMP SPECIFICATION					
1-1	Lamp Type		LED PAR38			
1-2	Dimmable (Y/N)		YES			
1-3	Base		E26			
1-4	Lamp Finish/Type	PAR38				
1-5	Lamp Wattage		17W			
1-6	Wattage Comparison (FC on Floor)		90W Incand (based on Floor Lux)			
1-7	Rated Average Life (hours) L70		25,000			
1-8	Reliable Operating Temperature		-4F to 113F		Wrenderve	
2	Photometric Characteristics					
2-1	Initial Lumens	1300				
2-2	Centre Beam Candle Power (Cd)		2350			
2-3	Beam Angle (50% I Max) in Degree		40		\sim	~
2-4	Beam Angle (10% I Max) in Degree		N/A		c(UL)us	Roffs Compliant
2-5	Initial Lumens per Watt		76			
2-6	Color Temperature		5000K			
2.7	Color Rendering Index (CRI)		80			
3	Electrical Characteristics					
3-1	Input Line Voltage/Frequency		120V 60 Hz	3-2	Power Factor	0.96
3-3	Lamp rated Wattage		17W	3-4	Input Line Current	160 mA
3-5	Total Harmonic Distortion		25%	3-6	Dimming Range in %	Full
4	Dimensional Characteristics					
4-1	Nominal Length (Inches/mm)		5.16"/131mm	4-2	Diameter	4.76"/121mm
5	Product Information					
5-1	Description 17W LED PAR38 Dimmable FLOOD - 5000K					
5-2	Primary Application	Household Use, Office & Commercial- Wet Location				
5-3	Warranty	5 Years fro	m date of purchase			
5-4	TCLP Compliant YES			5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	NO		5-8	UL / FCC	YES
6	PACKING DETAILS					
6-1	Color Box Size (Inches) 1x1	ize (Inches) 1x1 4.9 x 4.9 x 5		6-2	Inner Carton Size (Inches) 1x6	15.28 x 10.24 x 5.91
6-3	Master Carton Size (Inches) 1x12 21.46 x 16.0		2 x 7.28	6-4	Gross Weight / Net Weight (lbs)	8.49 / 5.07
04/2021© Overdrive For more information visit www.overdrive-lighting.com						
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.						