

## 6.5W LED R20 Dimmable - 3000K

Item # 722

**L6R20DIM/30K** 

|  | LLD by illiovation                 |  |     |                         | LUNZUDIIVI/ SUN           |  |
|--|------------------------------------|--|-----|-------------------------|---------------------------|--|
| 1  | LAMP SPECIFICATION                 |  |     |                         |                           |  |
| 1-1  | Lamp Type                          | LED R20 Bulb   |     |                         |                           |  |
| 1-2  | Dimmable (Y/N)                     | YES  |     |                         |                           |  |
| 1-3  | Base                               | E26 (Medium Base)  |     |                         |                           |  |
| 1-4  | Lamp Finish/Type                   | R20 Shape  |     |                         |                           |  |
| 1-5  | Lamp Wattage                       | 6.5W   |     |                         |                           |  |
| 1-6  | Wattage Comparison (FC on Floor    | ) 50W R20 Incand.  |     |                         |                           |  |
| 1-7  | Rated Average Life (hours) L70     | 25,000   |     |                         | <b>O</b> verdrive         |  |
| 1-8  | Reliable Operating Temperature     | -4F to 113F  |     |                         |                           |  |
| 2  | Photometric Characteristics        |  |     |                         |                           |  |
| 2-1  | Initial Lumens                     | 580  |     |                         |                           |  |
| 2-2  | Centre Beam Candle Power (Cd)      | 200  |     |                         |                           |  |
| 2-3  | Beam Angle (50%) in Degree         | 107  |     |                         | c(UL)us Rolls             |  |
| 2-4  | Initial Lumens per Watt            | 89   |     |                         | Gomphane                  |  |
| 2-5  | Color Temperature                  | 3000K  |     |                         |                           |  |
| 2-6  | Color Rendering Index (CRI)        | 80   |     |                         |                           |  |
| 3  | Electrical Characteristics         |  |     |                         |                           |  |
| 3-1  | Input Line Voltage/Frequency       | 120V 60 Hz   | 3-2 | Power Factor            | 0.90                      |  |
| 3-3  | Lamp rated Wattage                 | 6.5W   | 3-4 | Input Line Current      | 60mA                      |  |
| 3-5  | Total Harmonic Distortion          | 32%  | 3-6 | Dimming Range           | Full                      |  |
| 4  | <b>Dimensional Characteristics</b> |  |     |                         |                           |  |
| 4-1  | Nominal Length (Inches/mm)         | 3.93" / 100 mm   | 4-2 | Diameter                | 2.48" / 63 mm             |  |
| 5  | Product Information                |  |     |                         |                           |  |
| 5-1  | Description                        | 6.5W LED Dimmable R20 - 3000K                                  |     |                         |                           |  |
| 5-2  | Primary Application                | ry Application Household Use, Office, Agriculture & Commercial |     |                         |                           |  |
| 5-3  | Warranty                           | 5 Years from date of purchase                                  |     |                         |                           |  |
| 5-4  | TCLP Compliant                     | YES  | 5-6 | RoHS Compliant          | YES                       |  |
| 5-5  | Energy Star (Y/N)                  | No   | 5-7 | UL / FCC                | YES                       |  |
| 6  | PACKING DETAILS                    |  |     |                         |                           |  |
| 6-1  | Color Box Size (Inches) 1x1        | 2.6 x 2.6 x 4.3  | 6-2 | Inner Carton Size (Inch | nes) NA                   |  |
| 6-3  | Master Carton Size (Inches) 1x12   | 11.22 x 8.46 x 5.91  | 6-4 | Gross Weight / Net W    | eight ( lbs ) 2.73 / 1.54 |  |
| 04/2021© Overdrive For more information visit www.overdrive-lighting.com |                                    |  |     |                         |                           |  |

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.