



6.5W LED High CRI MR GU10 FLOOD - 3000K

Item # 680
L6HMRGUDIM/FL/30K



1 LAMP SPECIFICATION

1-1	Lamp Type	LED MRGU10
1-2	Dimmable (Y/N)	YES
1-3	Base	GU10
1-4	Lamp Finish/Type	MR16
1-5	Lamp Wattage	6.5W
1-6	Wattage Comparison (FC on Floor)	50W MR16
1-7	Rated Average Life (hours) L70	25,000
1-8	Reliable Operating Temperature	-4F to 113F

2 Photometric Characteristics

2-1	Initial Lumens	450
2-2	Centre Beam Candle Power (Cd)	630
2-3	Beam Angle (50% I Max) in Degree	40
2-4	Beam Angle (10% I Max) in Degree	NA
2-5	Initial Lumens per Watt	69
2-6	Color Temperature	3000K
2-7	Color Rendering Index (CRI)	90

3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.92
3-3	Lamp rated Wattage	6.5W	3-4	Input Line Current	60 mA
3-5	Total Harmonic Distortion	35%	3-6	Dimming Range in %	Full

4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	2.17" / 55 mm	4-2	Diameter	1.97" / 50 mm
-----	----------------------------	---------------	-----	----------	---------------

5 Product Information

5-1	Description	6.5W LED 90 CRI MR GU10 FLOOD - 3000K			
5-2	Primary Application	Household Use, Office & Commercial			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	ES	5-8	UL / FCC	YES

6 PACKING DETAILS

6-1	Color Box Size (Inche)	1x1	2 x 2 x 2.8	6-2	Inner Carton Size (cm)	1x12	6.42 x 4.33 x 5.98
6-3	Master Carton Size (Inche)	1x24	9.65 x 7.20 x 7.36	6-4	Gross Weight/Net Weight (lbs)	4.05 / 2.49	

02/2017© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.