



7W LED PAR20 Flood Dimmable - 5000K

Item # 737

L7PAR20DIM/FL/50K

1 LAMP SPECIFICATION

1-1	Lamp Type	LED PAR20
1-2	Dimmable (Y/N)	YES
1-3	Base	E26
1-4	Lamp Finish/Type	PAR20
1-5	Lamp Wattage	7W
1-6	Wattage Comparison (FC on Floor)	50W Incand (based on Floor Lux)
1-7	Rated Average Life (hours) L70	25,000
1-9	Reliable Operating Temperature	-4F to 113F



2 Photometric Characteristics

2-1	Initial Lumens	520
2-2	Centre Beam Candle Power (Cd)	800
2-3	Beam Angle (50% I Max) in Degree	40
2-4	Beam Angle (10% I Max) in Degree	N/A
2-5	Initial Lumens per Watt	74
2-6	Color Temperature	5000K
2-7	Color Rendering Index (CRI)	80

3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.96
3-3	Lamp rated Wattage	7W	3-4	Input Line Current	65mA
3-5	Total Harmonic Distortion	22%	3-6	Dimming Range in %	Full

4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	3.23"/82mm	4-2	Diameter	2.48"/63mm
-----	----------------------------	------------	-----	----------	------------

5 Product Information

5-1	Description	7W LED PAR20 Dimmable FLOOD - 5000K			
5-2	Primary Application	Household Use, Office & Commercial- Wet Location			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	NO	5-8	UL / FCC	YES

6 PACKING DETAILS

6-1	Color Box Size (Inches)	1x1	2.48 x 2.48 x 3.54	6-2	Inner Carton Size (Inches)	N/A
6-3	Master Carton Size (Inches)	1x12	10.83 x 8.19 x 4.80	6-4	Gross Weight / Net Weight (lbs)	2.16 / 1.45

05/2019© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.