

LED 100W 5000K High Bay (URSA Series)

Item # 400

DLC ID NO. - PKL2IJ9Z

CIVIT		CDE	CIFIC	ATION
1 – 1 X I	IIKE	VDF		Δ I II Δ

1-1	Fixture Type	LED High Bay
1-2	Dimmable (Y/N)	YES (1-10V)
1-3	Lamp Wattage	100W
1-4	Rated Average Life (hours) L70	50,000
1-5	LED Type	SMD

1-6 Reliable Operating Temperature -4F to 113F

2 Photometric Characteristics

2-1 Initial Lumens 14500

2-2 Initial Lumens per Watt 145

2-3 Color Temperature 5000K

2-4 Color Rendering Index (CRI) 80








B Electrical Characteristics

3-1 Input Line Voltage/Frequency 120V - 277V, 60 Hz 3-4 Power Factor >0.9

3-2 Lamp rated Wattage 100W 3-5 Dimming Type (1-10V)10-100%

3-3 Total Harmonic Distortion <20%

4 Dimensional Characteristics



Product Information

5-1 Primary Application Retrofit Application in Industrial / Commercial

5-2 Limited Warranty 5 Years from date of purchase

5-3 Certified UL/DLC/NEMA 4X

5-4 RoHS Compliant Yes

5-5 Environment Suitable for Damp Location/Indoor Use

6 Packing Details

6-1 Box size (Inch) 12.40 x 12.40 x 7.24 6-3 Net Weight (Kg/lbs) 1.95/4.30

6-2 Qty /Box 1 pcs 6-4 Gross Weight (Kg/lbs) 2.95/6.50

01/2024© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.