

LED 200W 5000K High Bay (URSA Series)

Item # 404

DLC ID NO. - P588C1F5

4	FIVTI	IDE	SPECIF		
	I FIXII	IKF '	VPF(II	-I(A I I	

1-1	Fixture Type	LED High Bay

- 1-2 Dimmable (Y/N) YES (1-10V)
- 1-3 Lamp Wattage 200W
- 1-4 Rated Average Life (hours) L70 50,000
- 1-5 LED Type SMD
- 1-6 Reliable Operating Temperature -4F to 113F

2 Photometric Characteristics

- 2-1 Initial Lumens 28000
- 2-2 Initial Lumens per Watt 140
- 2-3 Color Temperature 5000K
- 2-4 Color Rendering Index (CRI) 80








Electrical Characteristics

- 3-1 Input Line Voltage/Frequency 120V 277V, 60 Hz 3-4 Power Factor >0.9
- 3-2 Lamp rated Wattage 200W 3-5 Dimming Type (1-10V)10-100%
- 3-3 Total Harmonic Distortion <20%

4 Dimensional Characteristics



Product Information

- 5-1 Primary Application Retrofit Application in Industrial / Commercial
- 5-2 Limited Warranty 5 Years from date of purchase
- 5-3 Certified UL/DLC/NEMA 4X
- 5-4 RoHS Compliant Yes
- 5-5 Environment Suitable for Damp Location/Indoor Use

6 Packing Details

- 6-1 Box size (Inch) 14.88 x 14.88 x 8.19 6-3 Net Weight (Kg/lbs) 3.30/7.28
- 6-2 Qty /Box 1 pcs 6-4 Gross Weight (Kg/lbs) 4.20/9.26

01/2024© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.