| | verdrive | | | | |
|--|--------------------------------|---------------------------------------|-----------------------|--|--|
| | LED by Innovation | LED 65W Vapor Tight Linear | | OD R2-4VTM65WD-XXK | |
| 1 | FIXTURE SPECIFICATION | | | | |
| 1-1 | Fixture Type | LED Vapor Tight | | | |
| 1-2 | Dimmable (Y/N) | YES (1-10V) | | | |
| 1-3 | Lamp Wattage | 65W | ~ | | |
| 1-4 | Rated Average Life (hours) L70 | 50,000 | | | |
| 1-5 | LED Type | SMD | | | |
| 1-6 | Reliable Operating Temperature | -4F to 113F | | | |
| 2 | Photometric Characteristic | S | | | |
| 2-1 | Initial Lumens | 8450 | | | |
| 2-2 | Initial Lumens per Watt | 130 | | | |
| 2-3 | Color Temperature | 5000K | | Not all products are qualified on the D C OP! To view DIC multified or orducts | |
| 2-4 | Color Rendering Index (CRI) | 80 | | please consult the DLC qualified products please consult the DLC qualified products list at www.designlights.org/qpl | |
| 3 | Electrical Characteristics | | | | |
| 3-1 | Input Line Voltage/Frequency | 120V - 277V, 60 Hz | 3-4 Power Facto | or >0.9 | |
| 3-2 | Lamp rated Wattage | 65W | 3-5 Dimming T | ype (1-10V)10-100% | |
| 3-3 | Total Harmonic Distortion | <20% | | | |
| 4 | Dimensional Characteristic | 28 | | | |
| | LXBXH = 45.7" * 4.72" * 4.25" | | | | |
| 5 | Product Information | | | | |
| 5-1 | Primary Application R | etrofit Application in Industri | ial /Commercial | | |
| 5-2 | Limited Warranty 5 | Years from date of purchase | | | |
| 5-3 | Certified E | TL/DLC/NEMA 4X | | | |
| 5-4 | RoHS Compliant Y | 'es | | | |
| 5-5 | Environment S | Suitable for Damp Location/Indoor Use | | | |
| 6 | Packing Details | | | | |
| 6-1 | Box size (Inch) N | JA 6-3 | Net Weight (Kg/lbs) | NA | |
| 6-2 | Qty /Box 1 | pcs 6-4 | Gross Weight (Kg/lbs) | NA | |
| 01/2024© Overdrive For more information visit www.overdrive-lighting.com Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above. | | | | | |