



**10.5W LED 90CRI PAR30  
Dimmable FLOOD - 3000K**

**Item # 631**

**L10HPAR30DIM/FL/30K**



**1 LAMP SPECIFICATION**

1-1 Lamp Type	LED 90CRI PAR30
1-2 Dimmable (Y/N)	YES
1-3 Base	E26
1-4 Lamp Finish/Type	PAR30
1-5 Lamp Wattage	10.5W
1-6 Wattage Comparison (FC on Floor)	75W Incand (based on Floor Lux)
1-7 Rated Average Life (hours) L70	25,000
1-8 Reliable Operating Temperature	-4F to 113F

**2 Photometric Characteristics**

2-1 Initial Lumens	720
2-2 Centre Beam Candle Power (Cd)	1440
2-3 Beam Angle (50% I Max) in Degree	40(Flood)
2-4 Beam Angle (10% I Max) in Degree	N/A
2-5 Initial Lumens per Watt	69
2-6 Color Temperature	3000K
2.7 Color Rendering Index (CRI)	90

**3 Electrical Characteristics**

3-1 Input Line Voltage/Frequency	120V 60 Hz	3-2 Power Factor	0.96
3-3 Lamp rated Wattage	10.5W	3-4 Input Line Current	90 mA
3-5 Total Harmonic Distortion	18%	3-6 Dimming Range in %	Full

**4 Dimensional Characteristics**

4-1 Nominal Length (Inches/mm)	3.62"/92mm	4-2 Diameter	3.74"/95mm
--------------------------------	------------	--------------	------------

**5 Product Information**

5-1 Description	10.5W LED 90CRI PAR30 Dimmable FLOOD - 3000K		
5-2 Primary Application	Household Use, Office & Commercial - Wet location		
5-3 Warranty	5 Years from date of purchase		
5-4 TCLP Compliant	YES	5-6 RoHS Compliant	YES
5-5 Energy Star or LM79 (Y/N)	No	5-8 UL / FCC	YES

**6 PACKING DETAILS**

6-1 Color Box Size (Inches)	1x1	3.9 x 3.9 x 4.0	6-2 Inner Carton Size (Inches)	1x12	N/A
6-3 Master Carton Size (Inches)	1x12	16.65 x 12.60 x 6.22	6-4 Gross Weight / Net Weight ( lbs )	7.07 / 4.76	

01/2017© Overdrive For more information visit [www.overdrive-lighting.com](http://www.overdrive-lighting.com)

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.