



## 6.5W LED High CRI PAR20 Flood Dimmable - 3000K

**Item # 637**

**L6HPAR20DIM/FL/30K**

### 1 LAMP SPECIFICATION

1-1	Lamp Type	LED 90CRI PAR20
1-2	Dimmable (Y/N)	YES
1-3	Base	E26
1-4	Lamp Finish/Type	PAR20
1-5	Lamp Wattage	6.5W
1-6	Wattage Comparison (FC on Floor)	50W Incand (based on Floor Lux)
1-7	Rated Average Life (hours) L70	25,000
1-9	Reliable Operating Temperature	-4F to 113F



### 2 Photometric Characteristics

2-1	Initial Lumens	455
2-2	Centre Beam Candle Power (Cd)	620
2-3	Beam Angle (50% I Max) in Degree	40
2-4	Beam Angle (10% I Max) in Degree	N/A
2-5	Initial Lumens per Watt	70
2-6	Color Temperature	3000K
2-7	Color Rendering Index (CRI)	90



### 3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.91
3-3	Lamp rated Wattage	6.5W	3-4	Input Line Current	55mA
3-5	Total Harmonic Distortion	34%	3-6	Dimming Range in %	Full

### 4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	3.23"/82mm	4-2	Diameter	2.48"/63mm
-----	----------------------------	------------	-----	----------	------------

### 5 Product Information

5-1	Description	6.5W LED 90CRI PAR20 Dimmable FLOOD - 3000K			
5-2	Primary Application	Household Use, Office & Commercial- Wet Location			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	No	5-8	UL / FCC	YES

### 6 PACKING DETAILS

6-1	Color Box Size (Inches)	1x1	2.6 x 2.6 x 3.6	6-2	Inner Carton Size (Inches)	1x12	N/A
6-3	Master Carton Size (Inches)	1x12	11.54 x 8.78 x 4.92	6-4	Gross Weight / Net Weight ( lbs )	3.24 / 2.03	

01/2017© Overdrive For more information visit [www.overdrive-lighting.com](http://www.overdrive-lighting.com)

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.