





16.5W R40 Dimmable - 3000K

Item # 642

L16R40DIM/30K

| 1 LAMP SPECIFICATION | | | | |
|--|----------------------------------|------------------------------------|---------------------------------------|--|
| 1-1 | Lamp Type | LED R40 | |  |
| 1-2 | Dimmable (Y/N) | YES | | |
| 1-3 | Base | E26 | | |
| 1-4 | Lamp Finish/Type | R40 | | |
| 1-5 | Lamp Wattage | 16.5W | | |
| 1-6 | Wattage Comparison (FC on Floor) | 85W Incand | | |
| 1-7 | Rated Average Life (hours) L70 | 25,000 | | |
| 1-9 | Reliable Operating Temperature | -4F to 113F | | |
| 2 Photometric Characteristics | | | | |
| 2-1 | Initial Lumens | 1230 | |  |
| 2-2 | Centre Beam Candle Power (Cd) | 460 | | |
| 2-3 | Beam Angle (50% I Max) in Degree | 103 | | |
| 2-4 | Beam Angle (10% I Max) in Degree | N/A | | |
| 2-5 | Initial Lumens per Watt | 75 | | |
| 2-6 | Color Temperature | 3000K | | |
| 2-7 | Color Rendering Index (CRI) | 80 | | |
| 3 Electrical Characteristics | | | | |
| 3-1 | Input Line Voltage/Frequency | 120V 60 Hz | 3-2 Power Factor | 0.92 |
| 3-3 | Lamp rated Wattage | 16.5W | 3-4 Input Line Current | 140mA |
| 3-5 | Total Harmonic Distortion | 24% | 3-6 Dimming Range in % | Full |
| 4 Dimensional Characteristics | | | | |
| 4-1 | Nominal Length (Inches/mm) | 6.5"/164mm | 4-2 Diameter | 5"/127mm |
| 5 Product Information | | | | |
| 5-1 | Description | 16.5W LED R40 Dimmable - 3000K | | |
| 5-2 | Primary Application | Household Use, Office & Commercial | | |
| 5-3 | Warranty | 5 Years from date of purchase | | |
| 5-4 | TCLP Compliant | YES | 5-6 RoHS Compliant | YES |
| 5-5 | Energy Star or LM79 (Y/N) | No | 5-8 UL / FCC | YES |
| 6 PACKING DETAILS | | | | |
| 6-1 | Color Box Size (Inches) | 1x1 5.1 x 5.1 x 6.8 | 6-2 Inner Carton Size (Inches) | N/A |
| 6-3 | Master Carton Size (Inches) | 1x12 21.54 x 16.22 x 8.58 | 6-4 Gross Weight / Net Weight (lbs) | 9.32 / 5.29 |
| 01/2017© Overdrive For more information visit www.overdrive-lighting.com | | | | |
| Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above. | | | | |

