



14W LED EH80 Utility Luminaire Hard Wire - 5000K

Item # 652

L14EH80-W/HB/50K

1 LAMP SPECIFICATION

1-1	Lamp Type	EH80
1-2	Dimmable (Y/N)	NO
1-3	Base	With Hard Wire Connector
1-4	Lamp Finish/Type	EH80 Utility Light
1-5	Lamp Wattage	14W
1-6	Wattage Comparison (FC on Floor)	140W Incand/32W CFL
1-7	Rated Average Life (hours) L70	50,000
1-8	Reliable Operating Temperature	-4F to 113F



2 Photometric Characteristics

2-1	Initial Lumens	1440
2-2	Centre Beam Candle Power (Cd)	255
2-3	Beam Angle (50% I Max) in Degree	160
2-4	Beam Angle (10% I Max) in Degree	275
2-5	Initial Lumens per Watt	100
2-6	Color Temperature	5000K
2-7	Color Rendering Index (CRI)	80



3 Electrical Characteristics

3-1	Input Line Voltage/Frequency	120-277V 60 Hz	3-2	Power Factor	0.95
3-3	Lamp rated Wattage	14W	3-4	Input Line Current	125mA
3-5	Total Harmonic Distortion	<20%	3-6	Dimming Range in %	No

4 Dimensional Characteristics

4-1	Nominal Length (Inches/mm)	6.10" / 155 mm	4-2	Diameter	4.13" / 105 mm
-----	----------------------------	----------------	-----	----------	----------------

5 Product Information

5-1	Description	14W LED EH80 Utility Luminaire Hard Wire Connector - 5000K			
5-2	Primary Application	Commercial, Industrial, Agriculture, Refrigerator, Tunnel, Walk Way			
5-3	Warranty	5 Years from date of purchase			
5-4	TCLP Compliant	YES	5-6	RoHS Compliant	YES
5-5	LM79 (Y/N)	-	5-8	ETL - Wet Location	YES

6 PACKING DETAILS

6-1	Bulk Packing Size (Inches)	1x12	18.5 x 13.78 x 7.09	6-2	Gross Weight / Net Weight (lbs)	4.87 / 3.60
-----	----------------------------	------	---------------------	-----	-----------------------------------	-------------

03/2024© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.