



Indoor Ceiling Fixture ø 11.2X3" for MPLR, PMMA diffuser(21415-MN-BP6)

Item # 832

1 FIXTURE SPECIFICATION

| | | |
|-----|-------------------------------|-------------------|
| 1-1 | Fixture Type | Ceiling Fixture |
| 1-2 | Dimmable (Y/N) | Yes |
| 1-3 | Fixture Finish/Type | Empty Fixture |
| 1-4 | Fixture Wattage (*Variable) | 16/19/25W |
| 1-5 | Color | Sliver |
| 1-6 | LED Type | Module |
| 1-7 | Body Materials | Plastic/Aluminum |
| 2-1 | Diffuser | PMMA |
| 2-2 | Finishing Type | Painting |
| 2-3 | Color Temperature (*Variable) | 3000K/4000K/5000K |
| 2-4 | Color Rendering Index (CRI) | 80 |



*Variable depends on type of Overdrive MPLR used

3 Electrical Characteristics

| | | | | | |
|-----|------------------------------|------------------|-----|--------------|--------------|
| 3-1 | Input Line Voltage/Frequency | 120V | 3-4 | Power Factor | >0.90 |
| 3-2 | Lamp rated Wattage | 16W or 19 or 25W | 3-5 | Dimming Type | SCR, Digital |
| 3-3 | Total Harmonic Distortion | <40% | | | |

4 Dimensional Characteristics

| | | |
|-----|--------------|------|
| 4-1 | Width (Inch) | 2.95 |
| 4-2 | Height(Inch) | 11.1 |

5 Product Information

| | | |
|-----|---------------------|---------------------------------------|
| 5-1 | Primary Application | Residential/Hospitality |
| 5-2 | Limited Warranty | 5 Years from date of purchase |
| 5-3 | Certified | ETL/LM79 with Overdrive MPLR |
| 5-4 | RoHS Compliant | Yes |
| 5-5 | Environment | Suitable for Damp Location/Indoor Use |

6 Packing Details

| | | | | | |
|-----|--------------------|-----------------|-----|-----------|------|
| 6-1 | Master Carton Size | 20.28x12.4x12.4 | 6-3 | N.W. (Kg) | 2.30 |
| 6-2 | Qty /Box | 6 pcs | 6-4 | G.W. (Kg) | 3.30 |