






# 6W LED A Bulb Dimmable - 3000K Wet Location With Gasket

Item # 731

L6SA19DIM/30K

1 LAMP SPECIFICATION				
1-1	Lamp Type	LED A Bulb Dimmable		
1-2	Dimmable (Y/N)	YES		
1-3	Base	E26 (Medium Base)		
1-4	Lamp Finish/Type	A19 Shape		
1-5	Lamp Wattage	6W		
1-6	Wattage Comparison (FC on Floor)	40W Incand		
1-7	Rated Average Life (hours) L70	25,000		
1-8	Reliable Operating Temperature	-4F to 113F		
1-9	Wet Location Rated	YES		
1-10	Enclosed Fixture Rated	YES		
2 Photometric Characteristics				
2-1	Initial Lumens	545		
2-2	Centre Beam Candle Power (Cd)	145		
2-3	Beam Angle (50% I Max) in Degree	125		
2-4	Beam Angle (10% I Max) in Degree	210		
2-5	Initial Lumens per Watt	91		
2-6	Color Temperature	3000K		
2.7	Color Rendering Index (CRI)	>80		
3 Electrical Characteristics				
3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2 Power Factor	>0.90
3-3	Lamp rated Wattage	6W	3-4 Input Line Current	55mA
3-5	Total Harmonic Distortion	20%	3-6 Dimming Range in %	Full
4 Dimensional Characteristics				
4-1	Nominal Length (Inches/mm)	4.25" / 108 mm	4-2 Diameter	2.36" / 60 mm
5 Product Information				
5-1	Description	6W LED A Bulb Dimmable, 3000K, Medium Base - Wet Location		
5-2	Primary Application	Household Use, Office, Agriculture & Commercial		
5-3	Warranty	5 Years from date of purchase		
5-4	TCLP Compliant	YES	5-6 RoHS Compliant	YES
5-5	Energy Star or LM79 (Y/N)	LM79	5-8 UL / FCC	YES
6 PACKING DETAILS				
6-1	Color Box Size (Inches)	1x1 2.44 x 2.44 x 4.72	6-2 Inner Carton Size (cm) 1x12	10.35 x 7.72 x 5.12
6-3	Master Carton Size (Inches)	1x48 16.50 x 11.14 x 11.81	6-4 Gross Weight / Net Weight ( lbs )	12.08 / 7.50





10/2020© Overdrive For more information visit [www.overdrive-lighting.com](http://www.overdrive-lighting.com)

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.