

## 15W LED A Bulb Dimmable - 3000K Wet Location

Item # 705 L15WA21DIM/30K

AMP SPECIFICATION  amp Type  Dimmable (Y/N)  Base  amp Finish/Type  amp Wattage  Vattage Comparison (FC on Floor)  Bated Average Life (hours) L70				
Dimmable (Y/N) Base Bamp Finish/Type Bamp Wattage Wattage Comparison (FC on Floor) Bated Average Life (hours) L70	YES E26 (Medium Base) A21 Shape 15W 150W Incand (based on F			
dase amp Finish/Type amp Wattage Vattage Comparison (FC on Floor) dated Average Life (hours) L70	E26 (Medium Base) A21 Shape 15W 150W Incand (based on F			
amp Finish/Type amp Wattage Vattage Comparison (FC on Floor) lated Average Life (hours) L70	A21 Shape 15W 150W Incand (based on F			
amp Wattage Vattage Comparison (FC on Floor) tated Average Life (hours) L70	15W 150W Incand (based on F			
Vattage Comparison (FC on Floor) lated Average Life (hours) L70	150W Incand (based on F			
lated Average Life (hours) L70				
- , ,		·loor Lux)		
	25,000			
deliable Operating Temperature	-4F to 113			
Vet Location Rated	YES		<b>Ø</b> verd.	rivo
nclosed Fixture Rated	YES		over di	1176
Photometric Characteristics				
nitial Lumens	1450		- (7 L	
Centre Beam Candle Power (Cd)	345			
Beam Angle (50% I Max) in Degree	130		_	
nitial Lumens per Watt	97		(TI)	Paus
Color Temperature	3000K		Intertek	Compliant
Color Rendering Index (CRI)	82			
Electrical Characteristics				
nput Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	>0.90
amp rated Wattage	15W	3-4	Input Line Current	140mA
otal Harmonic Distortion	20%	3-6	Dimming Range in %	Full
Dimensional Characteristics				
Iominal Length (Inches/mm)	5.10" / 130 mm	4-2	Diameter	2.56" / 65 mm
Product Information				
Description	15W LED A Bulb Dimmable -3000K, Medium Base - Wet Location			
rimary Application	Agriculture ,Commercial kitchen, Household & Office use.			
Varranty	5 Years from date of purchase			
CLP Compliant	YES	5-6	RoHS Compliant	YES
nergy Star or LM79 (Y/N)	LM79	5-8	UL / FCC	YES
PACKING DETAILS				
olor Box Size (Inches) 1x1	2.67 x 2.67 x 5.43	6-2	Inner Carton Size (cm) 1x12	11.26 x 8.5 x 5.94
Master Carton Size (Inches) 1x48	17.71 x 12.71 x 11.81	6-4	Gross Weight / Net Weight ( lbs )	16.54 / 8.81
	Photometric Characteristics  Initial Lumens  Initial Lumens  Initial Lumens  Initial Lumens  Initial Lumens per Watt  Initial Lumens  Initial Lumens	chotometric Characteristics  chitial Lumens 1450 centre Beam Candle Power (Cd) 345 ceam Angle (50% I Max) in Degree 130 chitial Lumens per Watt 97 color Temperature 3000K color Rendering Index (CRI) 82 clectrical Characteristics comput Line Voltage/Frequency 120V 60 Hz camp rated Wattage 15W cotal Harmonic Distortion 20% commensional Characteristics cominal Length (Inches/mm) 5.10" / 130 mm coroduct Information covernity 5 Years from date of purchase CLP Compliant YES color Box Size (Inches) 1x1 2.67 x 2.67 x 5.43	Photometric Characteristics Initial Lumens 1450 Initial Lumens 1450 Initial Lumens 130 Initial Lumens per Watt 97 Initial Lumens	Inclosed Fixture Rated Photometric Characteristics Initial Lumens

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.